

100C72K10

Allen-Bradley 100C Contactor 37kW 3Pole 24VAC Coil 1NO
Contact Auxiliary



Allen-Bradley

by ROCKWELL AUTOMATION

CONTACTORS



Component type	Power contactor, AC switching
Range	100C
Model	N/A
Alternative	100E65KJ00

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

ELECTRICAL

Number of normally open contacts as main contact	3.0
Number of normally closed contacts as main contact	0.0
Rated operation current I_e at AC-3, 400 V	72.0 A
Rated operation power at AC-3, 400 V	40.0 kW
Rated operation current I_e at AC-1, 400 V	100.0 A
Max. rated operation voltage U_e AC	690.0 V
Voltage type for actuating	AC
Control supply voltage U_s at AC 50HZ	24.0 V
Number of auxiliary contacts as normally open contact	1.0
Number of auxiliary contacts as normally closed contact	0.0
Rated operation current I_e at AC-3, 690 V	42.0 A
Rated operation power at AC-3, 690 V	40.0 kW
Rated operation power at AC-4, 400 V	15.0 kW
Control supply voltage U_s at AC 60HZ	28.0 V
Power consumption, AC coil pickup	235.0 VA
Power consumption, AC coil hold-in	19.6 VA
Type of electrical connection of main circuit	Screw connection
Rated operation current I_e at AC-4, 400 V	31.0 A

CONSTRUCTION

Degree of protection (IP)	IP20
Mounting method	Screw mounting

DIMENSIONS

Height	122.0 mm
Width	81.0 mm
Depth	125.5 mm
Weight	1.47 kg