

1606XLP100E

Allen-Bradley 1606 Power Supply Compact 1Phase 100 to 240V
AC to 24 to 28V DC 100W 4.2A



Allen-Bradley

by ROCKWELL AUTOMATION

POWER SUPPLIES



Component type	DC-power supply
Range	1606
Model	N/A
Product status	Existing

The Allen-Bradley 1606 Switched Mode Power Supplies are the ideal solution for reliable and efficient power supply. Features compact design with wide input voltage range (single and multi phase AC and DC), power boosts, in-built redundancy and conformal coating for harsh environments. Available with multiple output voltage levels and wide power output range to accommodate various load sizes.

ELECTRICAL

Voltage type of supply voltage	AC/DC
Rated supply voltage at AC 50 Hz	100 - 240 V
Rated supply voltage at DC	220 - 375 V
Frequency	50 - 60 Hz
Nominal current (In)	1.0 A
Max. starting current	37.0 A
1st secondary output voltage	24 - 28 V
Max. output current 1	4.2 A
Nominal value output current 1	4.2 A
Nominal value output voltage 1	24.0 V
Power output	100.0 W
Power consumption	11.4 VA
Efficiency	90.0 %
Type of electric connection	Spring clamp connection
With LED indication	Yes
Secondary voltage adjustable	Yes
Rated supply voltage at AC 60 Hz	100 - 240 V
Output voltage stabilized	Yes

CONSTRUCTION

Rail mounting possible	Yes
Wall mounting possible	Yes
Degree of protection (IP)	IP20
Direct mounting possible	No
Degree of protection (NEMA)	Other

DIMENSIONS

Width	73.0 mm
Height	75.0 mm
Depth	103.0 mm

1606XLP100E

Allen-Bradley 1606 Power Supply Compact 1Phase 100 to 240V
AC to 24 to 28V DC 100W 4.2A



Allen-Bradley

by ROCKWELL AUTOMATION

POWER SUPPLIES

DIMENSIONS	Weight	0.36 kg
ENVIRONMENT	Operating temperature	-10 - 70 °C
	Stabilized	Yes