

# Alco

## Non-Metallic Conduit Fittings

### FEATURES:

- 2 piece nylon conduit fittings to suit 'Type NMUA' Anaconda conduit
- Reusable and durable connectors are flame retardant and resist salt water, weak acids, gasoline, alcohol, oil grease and common solvents
- Easy to install, by pushing the non-metallic conduit onto the smooth ferrule and tightening seal nut

<b>Applications</b>	For indoor and outdoor use
<b>Range</b>	C16/M16-FF- C32/M32/90A-FF
<b>Material</b>	Nylon 66
<b>Temperature Range</b>	-40°C to +100°C



### SPECIFICATIONS:

PART NUMBER	SIZE		THREAD SIZE (mm)	BODY STYLE	BOX QTY	SUITABLE CONDUIT
	mm	INCHES				
C16/M16-FF	16	3/8	16	Straight	25	NMUA38-30
C16/M16/90A-FF	16	3/8	16	90°	10	NMUA38-30
C20/M20-FF	20	1/2	20	Straight	25	NMUA12-30
C20/M20/90A-FF	20	1/2	20	90°	10	NMUA12-30
C25/M25-FF	25	3/4	25	Straight	10	NMUA34-30
C25/25/90A-FF	25	3/4	25	90°	10	NMUA34-30
C32/M32-FF	32	1	32	Straight	5	NMUA100-30
C32/M32/90A-FF	32	1	32	90°	5	NMUA100-30

**Wattmaster**

THE BRAND ELECTRICIANS RELY ON

T: 1300 300 747 F: 1300 300 074

[www.wattmaster.com.au](http://www.wattmaster.com.au)