## **Horizon S Series**

Residential metering enclosures for SA applications













- · Designed for both single and multi-phase installations.
- Provides safety, quality and performance.
- Suitable for domestic and light commercial metering applications.
- Easy-to-use gravity catch
- · Ratchet sliding cable entry
- RotaDIN rotating / removable DIN section.
  Cord retainer for easy retention of extension cords.
- Identification with covered labelling section.
- Weatherproof installation label for AS/NZS3000 compliance.
- Padlockable facility.
- External frame mounting brackets
- To suit type 1 and type 2 meter panel.
- Manufactured from 1.0 galvanised steel to Z275 or 316 stainless steel (S10/S).
- Powdercoated Light Grey RAL7035 or N4 surface finish.



## **ORDERING GUIDE - HORIZON S**

		Inclusions				Dimensions (mm)			Panel (mm)			
Part Number	DIN space	RCCB Link#	МСВ	Lock off	Meter neutral link	Height	Width	Depth	Height	Width	Depth Behind	
S10	24-pole	•	63A	•	•	690	485	278	350	365	75	
S10/S	24-pole	•	63A	•	•	690	485	278	350	365	75	
S20	24-pole	•	63A	•	•	860	485	278	590	365	75	

<sup>\*</sup> RCCB Links provides RCD expansion to 3 circuits

## **ORDERING GUIDE - COMBINED SERVICES**

		Enclosures		Inclusions		Dimensions (mm)			Panel (mm)			
Part Number	DIN space	S10	HZN/COM1^	Meter isolator	Panel	Metal pan	Height	Width	Depth	Height	Width	Depth Behind
S82*	24-pole	•	•	•	Type 1	•	1120	485	278	350	365	75

<sup>\*</sup> Electrical and Communications.

<sup>^</sup> For more information on the S10 enclosures see table above. For more information on the HZN/COM1 enclosures visit brenclosures.com.au.

ACCESSORIES					
Part Number	Description	S10	S10/S	S20	S82
HZN/PLINTH	Plinth suitable when wall mounting not possible	•		•	
HZN/ROOF	Roof for use in exposed weather applications	•		•	
CL	Coin lock (supplied with 2 keys, SAPN master key "series 97000")	•	•	•	•
HZN/FK8	Flush kit	•			