

## Fast Emergency Luminaire

### SALUTEM - LED Recessed Emergency Luminaire

An LED recessed non-maintained emergency downlight designed to provide discrete and outstanding emergency illumination with long life LED and low standby power consumption.

#### Features and Benefits

- Single LED with D63 emergency classification
- Lithium Ion battery including integrated battery management system (BMS) to maximise battery life
- Complete with flex and plug for easy installation
- Versatile two-piece disc with both large (144mm) and small disc (85mm)
- Designed and manufactured in accordance to AS/NZS 2293



Part Number: SATLI		
<b>Input</b>	<b>Operating Voltage</b>	230V
	<b>Frequency</b>	50Hz
<b>Output</b>	<b>LED Array</b>	Single LED
	<b>Light Source</b>	5W
	<b>Lifetime</b>	50,000 hour LEDs
	<b>Function</b>	Non-Maintained
	<b>Lumen Output (Emergency Mode)</b>	250lm
	<b>Power Consumption (LEDs)</b>	7.4W
<b>Battery</b>	<b>Type</b>	Li-Ion
	<b>Protection</b>	Overcharge and low voltage disconnect
	<b>Emergency Runtime</b>	3 hours*
<b>Physical</b>	<b>IP Classification</b>	IP20
	<b>Weight</b>	0.55kg
	<b>Dimensions - Lamp Disc (ØxH)</b>	Outer disc: 144x28mm / Inner disc: 85x28mm
	<b>Dimensions - Control Box (LxWxH)</b>	111x42x25mm
	<b>Construction</b>	Disc: Flame Retardant PC & Aluminum Heat Sink Control Box: Flame Retardant PC
<b>Installation</b>	<b>Mounting</b>	Recessed
<b>Environment</b>	<b>Temperature</b>	0°C - 40°C
	<b>Relative Humidity</b>	0 - 95%
<b>Conformance</b>	<b>C0</b>	D63
	<b>C90</b>	D63
	<b>Standards</b>	AS2293, CISPR15, AS60598
<b>Intelligence</b>	<b>Sentinel</b>	No
	<b>WiNetRF</b>	No
<b>Warranty</b>	<b>Duration</b>	Fitting: 3 Years / Battery: 1 Year

\*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
41511	Replacement Battery

SPACING TABLE	MOUNTING HEIGHT (m)			
	2.1	2.4	2.7	3.0
NATA Classification				
C0 – D63 (m)	11.5	13.2	14.8	16.5
C90 – D63 (m)	11.5	13.2	14.8	16.5

\*Refer to AS/NZ 2293 for complete spacing table.