

PRODUCT DATASHEET

SHALLOW JUNCTION BOXES

FEATURES

- Moulded PVC Junction Box, Grey Colour, Circular shape with screwed lid
- Use with PVC Cement to join with PVC Conduit
- Meets UL94V-0 flammability rating

SHALLOW JUNCTION BOXES 1 WAY ENTRY

ORDERING INFORMATION

ORDERING INFORMATION

| PART NO. | DESCRIPTION | UNIT | QTY |
|----------|---------------------------------------|------|-----|
| JB1-20 | JUNCTION BOX SHALLOW 20MM 1 WAY ENTRY | BOX | 10 |
| JB1-25 | JUNCTION BOX SHALLOW 25MM 1 WAY ENTRY | BOX | 10 |

•



PART NO. DESCRIPTION UNIT QTY

SHALLOW JUNCTION BOXES 2 WAY ENTRY

| JB2-20 | JUNCTION BOX SHALLOW 20MM 2 WAY ENTRY | BOX | 10 |
|--------|---------------------------------------|-----|----|
| JB2-25 | JUNCTION BOX SHALLOW 25MM 2 WAY ENTRY | BOX | 10 |
| | | | |

SHALLOW JUNCTION BOXES 3 WAY ENTRY ORDERING INFORMATION

| PART NO. | DESCRIPTION | UNIT | QTY |
|----------|---------------------------------------|------|-----|
| JB3-20 | JUNCTION BOX SHALLOW 20MM 3 WAY ENTRY | BOX | 10 |
| JB3-25 | JUNCTION BOX SHALLOW 25MM 3 WAY ENTRY | BOX | 10 |

SHALLOW JUNCTION BOXES 4 WAY ENTRY ORDERING INFORMATION

| PART NO. | DESCRIPTION | UNIT | QTY |
|----------|---------------------------------------|------|-----|
| JB4-20 | JUNCTION BOX SHALLOW 20MM 4 WAY ENTRY | BOX | 10 |
| JB4-25 | JUNCTION BOX SHALLOW 20MM 4 WAY ENTRY | BOX | 10 |



SHALLOW JUNCTION BOXES R/ANGLE ENTRY

ORDERING INFORMATION

| PART NO. | DESCRIPTION | UNIT | QTY |
|----------|---|------|-----|
| JB5-20 | JUNCTION BOX SHALLOW 20MM R/ANGLE ENTRY | BOX | 10 |
| JB5-25 | JUNCTION BOX SHALLOW 25MM R/ANGLE ENTRY | BOX | 10 |

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

T: 133 122 | F: 1300 303 310 | E: sales@cabac.com.au | W: cabac.com.au

