

STAINLESS STEEL TIES
STAINLESS STEEL PREMIUM TIES


- Resistant to hostile environments including chemicals
- Standard width and heavy-duty width available
- Improved fastening system and quick installation
- 20 years limited warranty



Part No.	Max Bundle Dia. (mm)	Approx. Length (mm)	Approx. Width (mm)	Min Loop Tensile Strength (kg)	Thickness (mm)	Unit	Qty
SST200/316	50	201	4.6	44	0.25	BOX	100
SST360/316	102	360	4.6	44	0.25	BOX	100
SST520/316	152	520	4.6	44	0.25	BOX	100
SST680/316	203	680	4.6	44	0.25	BOX	100

STAINLESS STEEL PREMIUM HEAVY DUTY TIES


- Resistant to hostile environments including chemicals
- Standard width and heavy-duty width available
- Improved fastening system and quick installation
- 20 years limited warranty



Part No.	Max Bundle Dia. (mm)	Approx. Length (mm)	Approx. Width (mm)	Min Loop Tensile Strength (kg)	Thickness (mm)	Unit	Qty
SST200-HD/316	50	201	7.9	113	0.25	BOX	50
SST360-HD/316	102	360	7.9	113	0.25	BOX	50
SST520-HD/316	152	520	7.9	113	0.25	BOX	50
SST680-HD/316	203	680	7.9	113	0.25	BOX	50
SST838-HD/316	254	838	7.9	113	0.25	BOX	50
SST1000-HD/316	298	1000	7.9	113	0.25	BOX	50
SST1500-HD/316	450	1500	7.9	113	0.25	BOX	50

STAINLESS STEEL STANDARD TIES


- Self-locking head design speeds installation and locks into place at any length along the body
- Provides a strong, durable method of cable bundling
- No water absorption
- Non-flammable
- SS316 material for most corrosive environments



Part No.	Max Bundle Dia. (mm)	Approx. Length (mm)	Approx. Width (mm)	Min Loop Tensile Strength (kg)	Thickness (mm)	Unit	Qty
SST200-316S	51	200	4.6	90	0.25	BOX	100
SST360-316S	102	360	4.6	90	0.25	BOX	100
SST520-316S	152	520	4.6	90	0.25	BOX	100
SST680-316S	203	680	4.6	90	0.25	BOX	100

STAINLESS STEEL STANDARD HEAVY DUTY TIES


- Self-locking head design speeds installation and locks into place at any length along the body
- Provides a strong, durable method of cable bundling
- No water absorption
- Non-flammable
- SS316 material for most corrosive environments



Part No.	Max Bundle Dia. (mm)	Approx. Length (mm)	Approx. Width (mm)	Min Loop Tensile Strength (kg)	Thickness (mm)	Unit	Qty
SST200-HD-316S	51	200	7.9	150	0.25	BOX	50
SST360-HD-316S	102	360	7.9	150	0.25	BOX	50
SST520-HD-316S	152	520	7.9	150	0.25	BOX	50
SST680-HD-316S	203	680	7.9	150	0.25	BOX	50
SST838-HD-316S	254	840	7.9	150	0.25	BOX	50
SST1000-HD-316S	300	1000	7.9	150	0.25	BOX	50
SST1500-HD-316S	465	1500	7.9	150	0.25	BOX	50