

**STAINLESS STEEL PREMIUM COATED TIES**


- 316 Stainless steel and buckle cable ties with a epoxy coating providing smooth surface and rounded edges for operator safety
- Halogen free Epoxy resin coat - durable, long lasting, for use in highly corrosive environments
- Certified to standard
- 20 year warranty



Part No.	Max Bundle Dia. (mm)	Approx. Length (mm)	Approx. Width (mm)	Min Loop Tensile Strength (kg)	Thickness (mm)	Unit	Qty
<b>STFC200-316</b>	50	201	4.6	45.4	0.25	BOX	100
<b>STFC360-316</b>	102	360	4.6	45.4	0.25	BOX	100

**STAINLESS STEEL PREMIUM COATED H/DUTY TIES**


- 316 Stainless steel and buckle cable ties with a epoxy coating providing smooth surface and rounded edges for operator safety
- Halogen free Epoxy resin coat - durable, long lasting, for use in highly corrosive environments
- Certified to standard
- 20 year warranty



Part No.	Max Bundle Dia. (mm)	Approx. Length (mm)	Approx. Width (mm)	Min Loop Tensile Strength (kg)	Thickness (mm)	Unit	Qty
<b>STFC200-HD-316</b>	50	201	7.9	113.4	0.25	BOX	50
<b>STFC360-HD-316</b>	102	360	7.9	113.4	0.25	BOX	50

**STAINLESS STEEL STANDARD COATED TIES**


- Polyester resin coated 316 stainless steel cable ties
- Very good tensile strength, durable method of cable bundling
- Rounded edges ensure cable protection and worker safety
- UV resistant, low smoke, halogen-free material, tested to standard



Part No.	Max Bundle Dia. (mm)	Approx. Length (mm)	Approx. Width (mm)	Min Loop Tensile Strength (kg)	Thickness (mm)	Unit	Qty
<b>STFC200-316S</b>	51	200	4.6	90	0.38	BOX	100
<b>STFC360-316S</b>	102	360	4.6	90	0.38	BOX	100

**STAINLESS STEEL STANDARD COATED H/DUTY TIES**


- Polyester resin coated 316 stainless steel cable ties
- Very good tensile strength, durable method of cable bundling
- Rounded edges ensure cable protection and worker safety
- UV resistant, low smoke, halogen-free material, tested to standard



Part No.	Max Bundle Dia. (mm)	Approx. Length (mm)	Approx. Width (mm)	Min Loop Tensile Strength (kg)	Thickness (mm)	Unit	Qty
<b>STFC200-HD-316S</b>	51	200	7.9	150	0.38	BOX	50
<b>STFC360-HD-316S</b>	102	360	7.9	150	0.38	BOX	50
<b>STFC520-HD-316S</b>	152	520	7.9	150	0.38	BOX	50
<b>STFC680-HD-316S</b>	203	680	7.9	150	0.38	BOX	50