

ARGO-1200-LP

CLEVERTRONICS LP ARGO LED WEATHERPROOF BATTEN WITH INTEGRAL BATTERY, SWITCHABLE COLOUR & OUTPUT



PRODUCT INFORMATION	.				
Part Number	ARGO-1200-LP				
MIC	AUB02320470001				
Description	LP Premium ARGO 1200mm LED Weatherproof Emergency Batten with Integral Battery, Switchable Colour and Output, Enabled with Clevertest Plus				
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)				
Mounting	Surface mount				
Dimensions L x W x H	1265mm x 121mm x 88mm				
Weight	2.6 kg				
Operating Mode	Sustained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery	Lithium Iron Phosphate, 3.2V 6400mAh				
Charging Method	Intelligent current limited constant voltage				
Diffuser	Polycarbonate				
Driver / Ballast	LED Driver – 40w Stallion, SP				
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80				
Operating Voltage	240V AC; 50Hz				
Total lumen output	4318lm (122lm/W @4000K, based on non-emergency), details see table Page 2				
Power Consumption	see table Page 2				
IP Rating	IP65				
Operating Temperature	0°C to 40°C				
Impact Rating	IK08				
AS2293 Classification	C ₀ =D63 C ₉₀ =D40				
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3				
Compliance Marking (RCM)					





ARGO-1200-LP

CLEVERTRONICS LP ARGO LED WEATHERPROOF BATTEN WITH INTEGRAL BATTERY, SWITCHABLE COLOUR & OUTPUT



REPLACEMENT PARTS					
PART NUMBER	DESCRIPTION				
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.				
AUM02370050001 CLIFE-PRO-CKIT-NP	Lifelight Pro, Control Only, 530mm, NP, CTP, OWC				
1330083	LED Driver - 40w Stallion, SP				
8002700	PCA:LED Strip 2S4P, Eco Argonaut (EM)				

Colour	Power Consumption					Lumen Output	
	High Output (700mA)		Low Output (350mA)		Ctondby	Hidh Output	Low Output
	MAX Charge	Standby	MAX Charge	Standby	Standby Lamp OFF	High Output (700mA)	Low Output (350mA)
	Lamp ON	Lamp ON	Lamp ON	Lamp ON			
3000K	40 W	38 W	22 W	20 W	0.4 W	3819 lm	2260 lm
4000K	38 W	36 W	21 W	19 W	0.4 W	4318 lm	2431 lm
5700K	40 W	38 W	22 W	20 W	0.4 W	4100 lm	2400 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

