



GLIDER

CLEVERTRONICS Glider Blade Exit, Recessed Mount, Trade Series,
Picto All, Double Sided



PRODUCT INFORMATION

Part Number	GLIDER
MIC	AUA03510120001
Description	Glider Blade Exit, Recessed Mount, Trade Series, Picto All, Double Sided
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Mount, Double Sided
Dimensions L x W x H	365mm x 95mm x 203mm
Weight	1.90kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box
Lamp/s	12 x Samsung LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 2.6 Watts (Max)
Earth Leakage	0.42
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E4, C90=E4, C180=E2.5, C270=E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560180	Battery
8003553	Emergency Driver
8012080	LED Board

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.