



### Main

Range	Clipsal Solis T Series
Product or component type	Switched socket
Product brand	Clipsal
Assembly Type	Complete product
Colour tint	Ebony aluminium
Protection	Shuttered
Main colour tint	Ebony aluminium

### Complementary

Control type	Rocker
Number Of Outlets	2
Socket-outlet type	Double socket-outlet
Mounting Type	Screw
Installation Type	Flush
Installation Orientation	Horizontal
Material	Aluminium
Surface finish	Metallic
[Ue] rated operational voltage	230/240 V AC
Network frequency	50 Hz
[In] rated current	10 A
Connections - terminals	4 x 2.5 mm <sup>2</sup> screw terminals 3 x 4 mm <sup>2</sup> screw terminals
Embedding depth	23.5 mm
Depth	27.4 mm
Height	74 mm
Width	148 mm
Mounting Centers	120 mm
Cut-out dimensions	130 x 50 mm
Surface treatment	Painted
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Wire stripping length	16 mm
Number of power socket outlets	2 x 2P + E, Australian/New Zealand
Cover Thickness	5 mm
Number Of Switches	2

### Environment

Product certifications	RCM
Standards	AS/NZS 3112
Relative humidity	10...95 %
Ambient air temperature for operation	0...45 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	6 cm
Package 1 Length	8 cm
Package 1 Weight	176 g
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	32.5 cm
Package 2 Width	25 cm
Package 2 Length	41 cm
Package 2 Weight	7.42 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>