

# Product data sheet Characteristics

# 1220S20

Screwed Conduit, Clipsal - Cable Management, 20mm, Brass Plug



#### Main

Product brand	Clipsal
Range of product	Series 1220S

#### Complementary

Material	Brass
Product destination	Diameter: 20 mm tube
Stub stiffness	Rigid

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.8 cm	
Package 1 Width	2 cm	
Package 1 Length	2 cm	
Package 1 Weight	17 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	20	
Package 2 Height	6.4 cm	
Package 2 Width	8.4 cm	
Package 2 Length	9 cm	
Package 2 Weight	390 g	

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	<b>☑</b> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.

This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental Disclosure Product Environmental Profile Circularity Profile No need of specific recycling operations

2