

Product data sheet

Characteristics

40RJ64SMT-TN

Modular jack, Actassi, RJ12, 40M, unshielded, translucent, bag x 1



Main

Range	Actassi
Product or component type	Telephone socket
Device presentation	Insert

Complementary

Device mounting	Flush
Provided equipment	Cable retention cap
Telephone socket type	RJ12 (4 contacts)
Cable stiffness	Solid
Colour tint	Translucent
Surface finish	Glossy
Type of packing	Polybag
Sale per indivisible quantity	1
Height	23 mm
Width	23 mm
Depth	28 mm
Net weight	0.006 kg
Standards	AS/NZS 3080 AS/CA S008

Environment

Product certifications	RCM
------------------------	-----

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	6.0 g
Package 1 Height	3.0 cm
Package 1 width	3.7 cm
Package 1 Length	4.7 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile