

Product data sheet

Characteristics

563J/50

single connector 40A 50/jar 500 VAC
translucent 3 x 6 mm² or 4 x 2.5 mm² cables



Main

Colour	Housing: transparent
Product brand	Clipsal
Provided equipment	1 x screw

Complementary

Rated voltage	500 V AC
Cable cross section	6 Mm ² solid or flexible 3 without cable end sleeve 2.5 mm ² 4
Connector type	Screw terminals
Contacts material	Brass
Material	Polypropylene: housing Zinc plated steel: screw

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	228.0 g
Package 1 Height	11 cm
Package 1 width	6.6 cm
Package 1 Length	6.7 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	2.28 kg
Package 2 Height	17.5 cm
Package 2 width	16 cm
Package 2 Length	24 cm

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.