

Product data sheet Characteristics

56C432-GY

56 Series Switched Socket Outlet - 32A - 4 Pin - 3 Pole Switch - 500V - Grey





Main

Series 56
Clipsal - 56 Series
Clipsal
Socket-outlet
Power supply
Grey (RAL 7035)

Complementary

Number of poles	4	
Plug, socket category	Low voltage	
Outlet standard	Australian/New Zealand	
Plug, socket, control station shape	Straight	
Number of modules	3	
Number of power socket outlets	1 protective cover	
[In] rated current	32 A	
[Ue] rated operational voltage	500 V AC 50 Hz	
Poles description	3P + E	
Protection type	Without protection	
Device mounting	Surface	
Material	Polycarbonate: cover	
Contacts material	Pins: phosphor bronze	
Connections - terminals	Screw terminals cable(s) 616 mm²	
Electrical connection	Industrial connector	
Depth	108 mm	
Width	101 mm	
Height	204 mm	
Targeted country	Australia	

Environment

Standards	AS/NZS 3133 AS/NZS 3123
Ambient air temperature for operation	-2575 °C
IP degree of protection	IP66 conforming to AS 60529

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	1.095 kg	
Package 1 Height	11.5 cm	
Package 1 width	10.5 cm	
Package 1 Length	20.8 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Life Is On