Product data sheet Characteristics

56K2SW320-GY

56 Series - Switch - Keylock - 3 Pole - 20A -500V - grey





Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Switch
Device presentation	Basic element with full cover plate
Device presentation Device application	Basic element with full cover plate Control
	'
Device application	Control

Complementary

Switch function	3-pole
Poles description	3P
[lcm] rated short-circuit making capacity	1 kA
Control type	Rotary knob
Number of poles	3
Device mounting	Surface
Fixing mode	By screws
Material	PC (polycarbonate)
Tightening torque	0.8 N.m
Local signalling	without
[Ue] rated operational voltage	500 V AC 50 Hz
Rated current	20 A
Marking	ON-OFF
Marking location	Marking on surface
Height	107 mm
Width	101 mm
Depth	112 mm
Net weight	0.62 kg
Breaking capacity	20 kA
Targeted country	Australia
Rotary handle padlocking	2 padlocks 8 mm
Actuator	Key
[lcw] rated short-time withstand current	1.2 kA for 1 s
[Uimp] rated impulse withstand voltage	4 kV
Motor M-rating AS3133	M200 at 500 V

Environment

Ambient air temperature for operation	-2575 °C	
IP degree of protection	IP66 conforming to AS 60529	
Standards	AS/NZS 3133	

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	612.0 g
Package 1 Height	11.25 cm
Package 1 width	11.25 cm
Package 1 Length	10.65 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Weight	7.44 kg
Package 2 Height	25 cm
Package 2 width	21.4 cm
Package 2 Length	33.8 cm

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Compliant EEU RoHS Declaration	
Yes	
₫Yes	
☑ China RoHS Declaration	
Product Environmental Profile	
	Compliant EU RoHS Declaration Yes China RoHS Declaration

Life Is On

2