

## Product data sheet Characteristics

# 56P310-EO

## Clipsal - 56 Series, Plug Top, Straight, 3 Flat PIN, 10A, 250V, IP66





#### Main

Widin	
Range	Clipsal - 56 Series
Range of product	Series 56
Product brand	Clipsal
Product or component type	Plug
Device application	Power supply
Number of poles	3

#### Complementary

[In] rated current	10 A	
Poles description	1P + N + E	
[Ue] rated operational voltage	250 V AC 50 Hz conforming to EN 60309-2	
Colour	Orange (RAL 2004)	
Material	Plastic	
Plug, socket category	Low voltage	
Material	Polycarbonate: housing	
Outlet standard	Industrial	
Connections - terminals	Screw terminal 0.751 mm²	
Wire stripping length	35 Mm	
	10 mm	
Contacts material	Pins: brass	
Cable entry	Cable gland	
Thread type	M20	
Plug, socket, control station shape	Straight	
Quality labels	RCM	
Pin arrangement	A	
Duration	6 h	
Net weight	0.12 kg	
Height	67 mm	
Width	67 mm	
Depth	112.5 mm	
Targeted country	Australia	

### Environment

IP degree of protection	IP66
Standards	AS/NZS 3112
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	11.2 cm
Package 1 Length	6.5 cm
Package 1 Weight	108 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	74 cm
Package 2 Width	118 cm
Package 2 Length	270 cm
Package 2 Weight	0.616 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	75
Package 3 Height	302 cm
Package 3 Width	350 cm
Package 3 Length	350 cm
Package 3 Weight	9.6 kg

## Offer Sustainability

Office Oddital lability		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure		

Life Is On