

Product data sheet Characteristics

56SO432-GY

56 Series Socket - 4 Pin - 32A - 500V - Grey





Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Grey (RAL 7035)
Outlet standard	Australian/New Zealand

Complementary

Plug, socket category	Low voltage
Device mounting	Surface
Mounting mode	External mounting
[In] rated current	32 A
[Ue] rated operational voltage	500 V AC 50 Hz conforming to EN 60309-2
Poles description	3P + E
Voltage colour	Black
Duration	7 h
Material	Polycarbonate: cover
Contacts material	Screws: brass
Connections - terminals	Screw terminals 416 mm² rigid or stranded cable
Tightening torque	0.8 N.m
Socket number	1
Socket-outlet type	N
Outlet standard	Industrial
Cable entry	1 tapped entry for cable gland
Net weight	0.58 kg
Depth	102 mm
Width	101 mm
Height	107 mm
Targeted country	Australia

Environment

Ambient air temperature for operation	-2575 °C
Standards	AS/NZS 3112

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	580.0 g	
Package 1 Height	11.6 cm	
Package 1 width	10.9 cm	
Package 1 Length	11 cm	

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Compliant	
Yes	
€Yes	
☑ China RoHS Declaration	
Product Environmental Profile	
	Compliant EVEU RoHS Declaration Yes China RoHS Declaration

Life Is On