

## Product data sheet Characteristics

# 56SSW2/10LE-GY

Switch Surface, Clipsal - 56 Series, IP66 2 Gang Single Pole 10A Less Enclosure



#### Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Switch
Assembly Type	Basic element with full cover plate
Device application	Control
Handle colour	Grey
Suitability for isolation	No
Colour	Cover: grey

#### Complementary

Poles description	1P
Control type	Sliding type
Number of poles	1
Installation Type	Surface
Material	PC (polycarbonate)
Tightening torque	0.8 N.m
Local signalling	without
[Ue] rated operational voltage	250 V AC 50 Hz
Rated current	10 A
Marking	ON-OFF
Marking location	Marking on surface
Targeted country	Australia
Height	107 mm
Width	101 mm
Depth	48 mm
Net weight	0.16 kg
Motor M-rating AS3133	M80 at 250 V
Switch function	1-pole
Rotary handle padlocking	2 padlocks 8 mm

### **Environment**

Ambient air temperature for operation	-2575 °C
IP degree of protection	IP56 conforming to AS 60529
Standards	AS/NZS 3133

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.2 cm	
Package 1 Width	10.0 cm	
Package 1 Length	10.1 cm	
Package 1 Weight	162.0 g	

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	