

## Product data sheet Characteristics

# EY56AI315

# Easy56, Appliance Inlet, 15A, 250V



Appliance inlet
Connection accessory
Connector Easy56 EY56CSC315
Low voltage
1P + N + E
3 pins
AC
Australian/New Zealand

### Complementary

Mounting mode	Surface mounted
Plug, socket, control station shape	Straight
[In] rated current	15 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Material	Polycarbonate: cover
Contacts material	Pins: brass
Connections - terminals	Screw terminals
Cable cross section	1.56 mm²
Cable stiffness	Rigid or stranded
Wire stripping length	10 mm
Net weight	0.471 kg
Height	101 mm
Width	101 mm
Depth	102 mm
Colour	Grey (RAL 7035)

#### Environment

Standards	AS/NZS 60320.1
Quality labels	RCM
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C
Ambient air temperature for storage	-2575 °C

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	11.2 cm	
Package 1 Width	10.4 cm	
Package 1 Length	10.6 cm	
Package 1 Weight	490 g	
Unit Type of Package 2	CAR	

Number of Units in Package 2	24
Package 2 Height	21.8 cm
Package 2 Width	35.3 cm
Package 2 Length	45 cm
Package 2 Weight	11960.84 g
Unit Type of Package 3	PAL
Number of Units in Package 3	480
Package 3 Height	100 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	253216.8 g

### Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	

Life Is On