

## Product data sheet

### Characteristics

# MX9E1111S

## Clipsal MAX9, Switchboard Enclosure, Type 1, 1 Row, 11 Ways, Surface Mounted



### Main

Range	MAX9
Product brand	Clipsal
Product or component type	Enclosure
Device application	Distribution
Number of 18 mm modules per row	11
Provided equipment	Earthing bar Neutral bar Circuit identification label Blanking plate
Colour	White electric (RAL 9003)
Door type	Tinted transparent door - upwards

### Complementary

Enclosure mounting	Surface
Number of horizontal rows	1
[Ue] rated operational voltage	240/415 V AC
[In] rated current	100 A
[Ui] rated insulation voltage	500 V
Number of ways	11 ways
Cable entry	Knock-out cable entries
Type of rail	DIN
Enclosure material	Housing: plastic Front face: plastic
Width	231 mm
Height	210 mm
Depth	113 mm

### Environment

Standards	AS/NZS 61439-3 AS/NZS 3000
Fire resistance	650 °C
IP degree of protection	IP30
IK degree of protection	IK05

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.4 cm
Package 1 Width	21.0 cm
Package 1 Length	23.5 cm
Package 1 Weight	1.434 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6

Package 2 Height	24.5 cm
Package 2 Width	39.0 cm
Package 2 Length	44.5 cm
Package 2 Weight	9.304 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	7-year
----------	--------