


Product data sheet Characteristics

P3025G

Clipsal Pro Series, Twin Power Point Grid, Horizontal Mount, 250V, 10A





Main	
Range	Pro Series
Product or component type	Switched socket
Device presentation	Mechanism with fixing frame
Outlet poles configuration	2P + E with shutter
Outlet standard	Australian

Complementary

Device mounting	Flush
Number of power socket outlets	2
Number of rocker	2
Range compatibility	Pro Series
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Fixing mode	By screws
Installation direction	Horizontal
Surface treatment	Untreated
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Rated current	10 A at 250 V AC 50 Hz
Connections - terminals	3 screw terminals
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Clamping connection capacity	1 x 2.54 x 2.5 mm² for rigid or stranded cable(s) 3 x 4 mm² for rigid or stranded cable(s)
Wire stripping length	16 mm
Material	PC (polycarbonate): fixing frame PP (polypropylene) POM (polyoxymethylene): shutter
Height	72 mm
Width	112 mm
Depth	36 mm
Net weight	0.078 kg

Environment

Ambient air temperature for operation	045 °C
Relative humidity	1095 %
Standards	AS/NZ 3112
Product certifications	RCM

Packing Units

•		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.6 cm	
Package 1 Width	7.2 cm	
Package 1 Length	11.2 cm	
Package 1 Weight	80.56 g	

Offer Sustainability

Oner oustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	[™] Yes	
Environmental Disclosure	☑ Product Environmental Profile	
-		

Life Is On