


Product data sheet

Characteristics

RMXE112S

Consumer switchboard, Resi MAX, 1 row, 12 modules, Surface



Main

Range	Resi MAX
Product brand	Clipsal
Product or component type	Enclosure
Enclosure type	Mini enclosure for modular device
Device application	Distribution
Number of 18 mm modules per row	12
Provided equipment	DIN rail Earth terminal block Neutral terminal block
Type of front cover	Plain
Colour	White (RAL 9003)
Door type	Plain door

Complementary

Enclosure mounting	Surface
Number of horizontal rows	1
[In] rated current	63 A
Number of ways	12 ways
Cable entry	Knock-out top and bottom Knock-out rear
Type of rail	35 mm asymmetrical rail
Number of terminal blocks	12 earth (screw connection) 14 neutral (screw connection)
Enclosure material	Technoplastic
Width	268 mm external
Height	228 mm external
Depth	101.5 mm external

Environment

Fire resistance	650 °C
IP degree of protection	IP40
IK degree of protection	IK07

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.9 kg
Package 1 Height	11.2 cm
Package 1 width	29.0 cm
Package 1 Length	27.0 cm
Unit Type of Package 2	P12
Number of Units in Package 2	90
Package 2 Weight	93.0 kg
Package 2 Height	80.0 cm

Package 2 width	80.0 cm
Package 2 Length	120.0 cm

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--------------------------------------------
