

## Product data sheet

### Characteristics

# CLITPFLS20SENLED

Floodlight LED, 20W, 4000K, 1800lm, Black, with Sensor



### Main

|                           |            |
|---------------------------|------------|
| Range                     | Clipsal    |
| Product or component type | Floodlight |
| Device application        | Lighting   |

### Complementary

|                                |                               |
|--------------------------------|-------------------------------|
| Type of installation           | Outdoor                       |
| Device mounting                | Surface                       |
| Total system power             | 20 W                          |
| Light source                   | LED                           |
| [Ue] rated operational voltage | 240 V AC 50 Hz                |
| Luminous flux                  | 1800 lm                       |
| Sensor detection angle         | 120°                          |
| Sensor detection range         | 12 m                          |
| Sensor time span               | 10 min                        |
| Colour rendering index         | R <sub>a</sub> =70            |
| Bulb lifespan                  | 30000 h                       |
| Colour temperature             | 4000 K                        |
| Beam angle                     | 100 °                         |
| Electrical insulation class    | Class I                       |
| Height                         | Body with trunion arm: 235 mm |
| Width                          | 116 mm                        |
| Depth                          | 29 mm                         |
| Net weight                     | 0.75 kg                       |
| Cable length                   | 0.9 m                         |

### Environment

|                                       |                          |
|---------------------------------------|--------------------------|
| IP degree of protection               | IP65                     |
| Ambient air temperature for operation | -10...40 °C              |
| Relative humidity                     | 10...95 % non-condensing |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 1.33 kg |
| Package 1 Height             | 23 cm   |
| Package 1 width              | 6 cm    |

|                              |         |
|------------------------------|---------|
| Package 1 Length             | 21 cm   |
| Unit Type of Package 2       | CAR     |
| Number of Units in Package 2 | 10      |
| Package 2 Weight             | 10.9 kg |
| Package 2 Height             | 24 cm   |
| Package 2 width              | 40.4 cm |
| Package 2 Length             | 55 cm   |

### Contractual warranty

|          |         |
|----------|---------|
| Warranty | 3-Years |
|----------|---------|