

# Product data sheet Characteristics

# WSC227/1/15-RG SOCKET SWITCHED SINGLE WEATHER PROTECTED 15A 250V





#### Main

Man		
Range of product	Weathershield	
Product brand	Clipsal	
Colour	Resistant grey	

### Complementary

Control type	Sliding type ON/OFF button
Number of gangs	1 gang
Pin number	3
Number of power socket outlets	1
Fixing mode	By screws
Local signalling	Without light indicator
Mounting position	Horizontal
Material	Plastic
[Ue] rated operational voltage	250 V AC
[In] rated current	15 A
Length	115 mm
Width	85 mm
Fixing center	84 mm

#### Environment

IP degree of protection	IP53
Standards	AS/NZS 3112:approval number S/1

## **Packing Units**

PCE
1
242 g
8.6 cm
9 cm
12 cm
CAR
50
12.5 kg
24.6 cm
42.4 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Length	43.8 cm	
Unit Type of Package 3	PAL	
Number of Units in Package 3	600	
Package 3 Weight	172 kg	
Package 3 Height	110 cm	
Package 3 width	114 cm	
Package 3 Length	114 cm	

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	<sup>™</sup> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Life Is On