



A2

A2 Single Seal Industrial Cable Gland with 20-24mm Length of Entry

For all types of Unarmoured & Braided Cables

- High quality durable materials
- Robust, heavy duty design
- Displacement type seal
- Deluge protected
- -60°C to +130°C (standard), -20°C to 200°C (ThermIn option page 91)



Gland shown as sold with locknut and IP entry thread washer

TECHNICAL DATA

Design Specification	BS 6121:Part 1:1989, IEC 62444, EN 62444
Mechanical Classifications*	Impact = Level 8, Cable Anchorage = Class B
Enclosure Protection	IK10 to IEC 62262 (20 joules)
CSA Certificate	1211841
Code of Protection	Enclosure Type 4X
Marine Approvals	LRS: 01/00171 (E1), ABS: 16-LD1472056-PDA
GOST R Certificate	POCC GB.AT35.H00102
Ingress Protection Rating**	IP66, IP67 & IP68***
Deluge Protection Compliance	DTS01 : 91
Cable Gland Material	Electroless Nickel Plated Brass
Seal Material	CMP Thermoset Rubber
Cable Type	Unarmoured & Braided when terminated inside enclosure
Sealing Technique	CMP Unique Displacement Seal Concept
Sealing Area(s)	Cable Outer Sheath

* Mechanical & Electrical Classifications applied as per IEC 62444 & EN 62444

** When CMP installation accessories are used. Refer to page 7 or www.cmp-products.com for further information.

*** IP68 tested to a minimum depth of 30 metres for 12 hours, alternate depths / durations can be provided upon request

Cable Gland Selection Table

Refer to illustration at the top of the page.

Cable Gland Size	Available Entry Threads "C" (Alternate Thread Lengths Available)		Overall Cable Diameter "A"		Across Flats "D" Max	Across Corners "D" Max	Protrusion Length "F"	Combined Ordering Reference (*Nickel Plated Brass Metric)			Shroud	Cable Gland Weight (Kgs)
	Standard		Min	Max				Size	Type	Ordering Suffix		
	Metric	Thread Length "E"										
20S16	M20	20.0	3.2	8.7	24.0	26.4	25.1	20S16	A2	A21RA5/A20LOE	PVC04	0.070
20S	M20	20.0	6.1	11.7	24.0	26.4	25.1	20S	A2	A21RA5/A20LOE	PVC04	0.060
20	M20	20.0	6.5	14.0	27.0	29.7	27.2	20	A2	A21RA5/A20LOE	PVC05	0.070
25	M25	20.0	11.1	20.0	36.0	39.6	35.5	25	A2	A21RA5/A20LOE	PVC09	0.130
32	M32	20.0	17.0	26.3	41.0	45.1	34.2	32	A2	A21RA5/A20LOE	PVC10	0.150
40	M40	20.0	23.5	32.2	50.0	55.0	35.1	40	A2	A21RA5/A20LOE	PVC13	0.200
50S	M50	20.0	31.0	38.2	55.0	60.5	32.0	50S	A2	A21RA5/A20LOE	PVC15	0.260
50	M50	20.0	35.6	44.0	60.0	66.0	36.3	50	A2	A21RA5/A20LOE	PVC18	0.270
63S	M63	20.0	41.5	49.9	70.5	77.6	33.5	63S	A2	A21RA5/A20LOE	PVC21	0.430
63	M63	20.0	47.2	55.9	75.0	82.5	35.8	63	A2	A21RA5/A20LOE	PVC23	0.460
75S	M75	20.0	54.0	61.9	84.0	92.4	34.2	75S	A2	A21RA5/A20LOE	PVC24	0.520
75	M75	20.0	61.1	67.9	84.0	92.4	40.6	75	A2	A21RA5/A20LOE	PVC24	0.500
90	M90	24.0	66.6	79.9	108.0	118.8	58.3	90	A2	A21RA5/A	PVC31	1.600
100	M100	24.0	76.0	91.0	123.0	135.3	55.2	100	A2	A21RA5/A	LSF33	1.780
115	M115	24.0	86.0	97.9	133.4	146.7	65.2	115	A2	A21RA5/A	LSF34	2.670
130	M130	24.0	97.0	114.9	152.4	167.6	73.9	130	A2	A21RA5/A	LSF35	3.800

Dimensions are displayed in millimetres unless otherwise stated