

INDUSTRIAL CANOPY LED LOW BAY



TECHNICAL

Light Source:	Phillips Lumileds			
Body:	Aluminium			
Colour Temperature:	5700K Cool White			
Average LED and Control Gear Life:	>50,000 hrs			
Beam Angle:	120° degrees (Symmetrical)			
Efficacy:	130 Lm/W			
CRI:	> 70			
Max Junction Temperature:	150C			
Thermal Management:	Aluminium Heatsink			
Cooling:	Conduction, Convection			
Operating Range Tc:	-35°c to 55°c			



ELECTRICAL

Power Supply Constant Current:	Mean Well HLG				
Protection:	Over Voltage, Short Circuit and Over Temperature				
Power Factor:	> 0.95				
Ingress Protection Rating:	IP65				
Impact Rating:	IK08				
Certification:	RCM, EMC, CE,				
Warranty:	3 Years				



FEATURES

- High Quality Construction
- Mean Well HLG Driver
- Phillips Lumileds LED chips
- High Lumen Output 130 Lm/W
- IP65 Protected against water exposure
- 3 Year Warranty



ORDER CODES

UNDER GUDES					Size (in mm)		
Model	Wattage	Light Colour	Lumens	Weight	Α	В	С
COR-75	75 watts	Cool White 5700k	9,750Lm	4.8kg	420	420	100
COR-110	110 watts	Cool White 5700k	14,300Lm	5.1kg	420	420	100
COR-150	150 watts	Cool White 5700k	19,500Lm	5.1kg	420	420	100

ACCESSORIES

COR-RC Recessed Canopy Plate - Custom sizes available



SMARTER LIGHTING SOLUTIONS

IQ Lighting Australia 6/24 Yalgar Rd, Kirrawee NSW 2232 www.iqlighting.com.au 1300 475 444

Technical Data sheets available on request. Model appearance may vary. July 2020 specifications are subject to change without prior notice.