


# CENTAURI 10/15

C10/15W150R-MULTI

SAP CODE: 2001195




10/15W, dual intensity, three colour temperature LED shoplight

A versatile high output downlight with switchable colour temperatures and intensity.



Photometric Diagram



Unit: cd  
 - C0/180 100.0deg  
 - C90/270 100.0deg

## KEY INFORMATION

Lumen Output 15W	1440 / 1520 / 1490lm
- Low Power Mode 10W	1010 / 1090 / 1090lm
Input Power	15W
Hole Cutout Size	Ø105-135mm
Dimming Options	*Phase-Cut Dimming
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP44
IK Rating	N/A
IC Rating	IC-4
Rebate Scheme Approvals	N/A

## PHOTOMETRIC

Efficacy 15W	96 / 101 / 99lm/W
- Low Power Mode 10W	101 / 109 / 109lm/W
LED	SMD
CCT	3000 / 4000 / 5000K
CRI	>80
Beam Angle	100°

## ELECTRICAL

Driver	Remote
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	29VDC
Power Factor	>0.9
LED Input Current (nominal)	350-500mA
Useful life @Ta25° (L70)	50,000hr

## CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Rubberised Clip
Connection Type	1.1m Flex & Plug
Total Weight	0.75kg
Dimensions	Ø150x35mm
Operating Ambient Temp.	-20 to 40°C
Electrical Classification	Class 2

\*Dimming performance may vary depending on the specifications of the dimmer being used. For best performance use the Haneco DUO-350W dimmer.