



# STAX 20W

STAX20WB5K

SAP CODE: 2001648



Photometric Diagram



Unit: cd  
 - C0/180 110.0deg  
 - C90/270 110.0deg

## 20W, Slimline LED floodlight

A compact and stylish LED floodlight for general area lighting.

### KEY INFORMATION

Lumen Output	2070lm
Input Power	20W
Hole Cutout Size	N/A
Install	<b>SURFACE MOUNT</b>
Dimming Options	Non-Dimmable
Trim Colour	BLACK
Warranty	3yr
IP Rating	IP65
IK Rating	IK07
IC Rating	N/A
Rebate Scheme Approvals	

### PHOTOMETRIC

Efficacy	104lm/W
LED	SMD
CCT	5000K
CRI	>80
Beam Angle	110°

### ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	N/A
Power Factor	>0.9
LED Input Current (nominal)	N/A
Useful life @Ta25° (L70)	50,000hr

### CONSTRUCTION

Housing	Aluminium + Polycarbonate
Optics	Polycarbonate Diffuser
Adjustable Angle	0-180°
Fixings/Hardware	Bracket
Connection Type	1m Flex
Total Weight	0.5kg
Dimensions	194 x 143 x 32mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1