



## ECFLED-LI

CLEVERTRONICS ECONOMY LITHIUM CLEVERFIT EXIT



PRODUCT INFORMATION	
Part Number	ECFLED-LI
MIC	AUA03510040001
Description	Economy Lithium Cleverfit Emergency Exit
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.2kg
Operating Mode	Can be toggled between maintained and non-maintained mode by pressing the test button 5 times within a 4 second period - default setting is maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 600mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	4 x LED, 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.1 Watts (Standby), 2.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2 C90=E2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550195	BATT: LiFePO4 3.2V 600mAh 210mm lead, noBRKT
8002900	PCA:LED Strip ECFLED-LI CT10242-D1
8002881	PCA: Driver ECFLED-LI CT10240-L6 4C40 M/NM CF 345

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.