



RCBO 1P 6kA C-32A 30mA A

ADA132T

Architecture

Neutral position	right
Number of protected poles	1
Number of poles	1 P
Type of pole	1 P
Fixing mode	DIN rail type O (symmetrical)
Curve	C

Functions

Concurrently switching N-neutral	no
Sealable	yes

Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

Controls and indicators

With Contact position indicator	yes
With fault indicator	no

Connectivity

Top connection alignment for modular devices	Shifted terminal
Bottom connection alignment for modular devices	Aligned terminal

Main electrical features

Rated operational voltage Ue	230 / 240 V
Type of supply voltage	AC

Voltage

Rated insulation voltage	250 V
Max operating voltage	253 V
Rated impulse withstand voltage	4000 V

Electric current

Rated residual operating current	30 mA
Rated current	32 A
Withstand not tripping on 8-20 ?s wave	3 kA
Breaking and opening capacity	6 kA
min/maxi threshold value of the AC thermal operation	1,13 / 1,45 I _n
Magnetic regulating current	5 / 10 I _n
Rated short circuit breaking capacity I _{cn} under 230V AC according IEC 61009-1	6 kA
Rated short circuit breaking capacity I _{cn} under 240V AC according IEC 61009-1	6 kA
Rated service breaking capacity I _{cs} under 230V AC according IEC 61009-1	6 kA
Rated service breaking capacity I _{cs} under 240V AC according IEC 61009-1	6 kA

Electric current / temperature

Rating current -25°C	40,06 A
Rating current -20°C	39,39 A
Rating current -15°C	38,72 A
Rating current -10°C	38,03 A
Rating current -5°C	37,33 A
Rating current 0°C	36,62 A
Rating current 5°C	35,89 A
Rating current 10°C	35,14 A
Rating current 15°C	34,39 A
Rating current 20°C	33,61 A
Rating current 25°C	32,81 A
Rating current 30°C	32 A
Rating current 35°C	31,16 A
Rating current 40°C	30,31 A
Rating current 45°C	29,42 A
Rating current 50°C	28,51 A
Rating current 55°C	27,57 A
Rating current 60°C	26,6 A

Current correction factors

Correction factor of rating current for 2 devices placed 1 side-by-side	1
Correction factor of rating current for 3 devices placed 0,95 side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85

Frequency

Frequency	50 Hz
-----------	-------

Power

Total power loss under I _N	9,63 W
Power loss per pole at I _n	5,53 W

Endurance

Electric endurance in number of cycles	1000
Number of mechanical operations	2000

Dimensions

Depth of installed product	70 mm
Height of installed product	115 mm
Width of installed product	17,5 mm

Installation, mounting

Type of top connection for modular devices	with screw
Type of bottom rail clip for modular devices	metallic isolated
Type of Bottom Connection for modular devices	Blconnect
Top removability for modular devices	no
Bottom removability for modular devices	no
Suitable for flush-mounting	yes
360° product mounting position	yes

Connection

Connection cross-section at output with screw, for flexible conductor	1 / 16 mm ²
Connection cross-section at output with screw, for massive conductor	1 / 25 mm ²
Connection cross-section for rigid conductor, upstream terminals with screws	1 / 16 mm ²
Connection cross-section of the access with screws, with flexible conductor	1 / 10 mm ²
Downstream cage clamp delivery status	opened
Upstream cage clamp delivery status	opened
Nominal tightening torque bottom terminal	3,2 Nm
Nominal tightening torque top terminal	2,1 Nm

Cable

Length of conductors used for the heating test (m) according to product standard	1 m
Conductor cross-section used for heating test(mm ²) according to product standard	6 mm ²

Equipment

Quick connect	no
Can be accessorized	no
Accept terminal cover	no
With transparent product label holder	no

Standards

European directive WEEE	concerned
-------------------------	-----------

Safety

Protection index IP	IP20
Residual current type	A

Use conditions

Operating temperature	-5 60 °C
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I ² t	3
Altitude	2000 m
Air humidity protection	Execution II
Storage/transport temperature	-25 60 °C

temperatur

Temperature of calibration	30 °C
Ambient air temperature during heating test according to the product standard	22,8 °C
Max. admissible temperature on accessible parts (intended to be touched)	59,8 °C
Max. admissible temperature on accessible parts (manual operating means)	50 °C
Max. admissible temperature on access. parts (not touched for normal operation)	68,7 °C
Max. admissible temperature on terminals	67,2 °C
Temp.-rise limits for access. parts (toggle) according to product standard	25 K
Temp.-rise limits for access. parts (not touched) according to product standard	60 K
Temp.rise limits for access. parts (to be touched) according to product standard	40 K
Temperature-rise limits for terminals according to the product standard	65 K
Temperature-rise measured on accessible parts at In (manual operating means)	10 K
Temperature-rise measured on access. parts at In (not touched normal operation)	28,7 K
Temperature-rise measured on accessible parts at In (intended to be touched)	19,8 K
Temperature-rise measured on terminals at In	27,2 K