

JVC7200S16TW

## 160A TPN board, INVICTA, 72P Chassis

| Architecture                   |                       |
|--------------------------------|-----------------------|
| Fixing mode                    | surface-mounting      |
| Functions                      |                       |
| Overvoltage protection         | no                    |
| Main electrical features       |                       |
| Nominal voltage                | 400 V                 |
| Electric current               |                       |
| Rated current                  | 160 A                 |
| Cover, door                    |                       |
| Type of door closing           | with keylock          |
| Interlockable                  | no                    |
| Number of keylock of the door  | 2                     |
| Cover type                     | Closed (plain)        |
| Door leave                     | single                |
| Cover type                     | Door                  |
| Transparent cover or door      | no                    |
| Materials                      |                       |
| Colour                         | light grey            |
| RAL colour                     | RAL 7035 - Light grey |
| Material                       | Steel                 |
| Type of surface treatment      | powder-coated         |
| Dimensions                     |                       |
| Insertion depth                | 117 mm                |
| Depth of installed product     | 135 mm                |
| Internal depth                 | 115 mm                |
| Height of installed product    | 1235 mm               |
| Width of installed product     | 480 mm                |
| Thickness of sidewall material | 1,2 mm                |

## Installation, mounting

| Suitable for outdoor use                     | no                          |
|--|-----------------------------|
| Accessories included                         |                             |
| Mounting plate included                      | no                          |
| With lock                                    | yes                         |
| Equipment                                    |                             |
| Quantity of rails                            | 1                           |
| Extension possible                           | yes                         |
| Safety                                       |                             |
| IK protection code against mecanical impacts | 05                          |
| Protection index IP                          | IP30                        |
| Protection class                             | isol.class I                |
| Glow wire test                               | according to AS/NZS 61439-1 |
| Fire resistance                              | -                           |
|  |                             |