



## 1P 40A Switch , Red Toggle

Similar image  
(Picture shows SBR163)

### Architecture

Type of order	Break switch
Neutral position	without neutral
Number of poles	1 P
Type of pole	1 P

### Main electrical features

Rated operational voltage Ue	230 V
Frequency	50/60 Hz

### Voltage

Rated insulation voltage	440 V
Type of voltage input 1	AC
Rated impulse withstand voltage	6000 V

### Electric current

Rated operational current in AC21 category B	40 A
Acceptable current rating with AC22 category A	40 A
Rated current	40 A
Rated short-time withstand current 1s	0,6 kA
Thermal rated current outside of housings	40 A
Rated operational current in AC21 category A	40 A
Acceptable current rating with AC22 category B	40 A
Rated short-circuit making capacity Icm under 240V AC according IEC 60947-3	846 A

### Frequency

Frequency	50 to 60 Hz
-----------	-------------

### Power

Total power loss under IN	1,1 W
Power loss per pole at In	1,1 W

#### Endurance

Electrical durability at nominal load in AC21 in operating cycles	5000
Electrical durability at nominal load in AC22 in operating cycles	5000
Number of mechanical operations	60000

#### Dimensions

Depth of installed product	68 mm
Height of installed product	83 mm
Width of installed product	17,5 mm

#### Installation, mounting

Tightening torque	2,8Nm
-------------------	-------

#### Connection

Connection cross-sect. flexible conductor	2,5 / 16mm <sup>2</sup>
Connection cross-sect. rigid cable	2,5 / 25mm <sup>2</sup>
Cage clamp position	in line
Type of connection	with screw

#### Equipment

Quantity of NO contacts	1
-------------------------	---

#### Standards

Standard text	IEC 60947-3, IEC/EN 60669-2, IEC/EN 60669-4
European directive WEEE	not concerned

#### Safety

Protection index IP	IP20
---------------------	------

#### Use conditions

Operating temperature	-20 50 °C
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Altitude	2000 m
Storage/transport temperature	-40 80 °C