



Sm.distr, IC<sup>2</sup>, surface, 2M, w/o door

VD102NT

#### Architecture

Fixing mode	surface-mounting
-------------	------------------

#### Functions

With a pipe-in lead	yes
---------------------	-----

#### Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

#### Main electrical features

Nominal voltage	400 V
-----------------	-------

#### Electric current

Rated current	63 A
---------------	------

#### Cover, door

Type of door closing	non keylock
Interlockable	no
Cover type	Closed (plain)
Transparent cover or door	no

#### Materials

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

#### Dimensions

Depth of installed product	71 mm
Internal depth	72 mm
Height of installed product	163,5 mm
Width of installed product	45,5 mm
Width in division units	2

#### Installation, mounting

Suitable for outdoor use	no
--------------------------	----

#### Accessories included

Mounting plate included	no
With lock	no

#### Equipment

Number of rows	1
Quantity of section in width	1
Quantity of rails	1
Can be accessorized	yes
Extension possible	no

#### Standards

European directive WEEE	not concerned
-------------------------	---------------

#### Safety

IK protection code against mechanical impacts	IK07
Protection index IP	IP30
Protection class	isol.class II
Halogen free	yes
Ultraviolet resistant	no

#### Use conditions

Operating temperature	-25 40 °C
-----------------------	-----------