



Similar image
(Picture shows VE312F)

vector, IP65,48M, UV-stable, DC/AC

Architecture

Fixing mode	surface-mounting
-------------	------------------

Functions

With a pipe-in lead	yes
---------------------	-----

Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

Main electrical features

Nominal voltage	400 V
-----------------	-------

Cover, door

Cover type	Closed (plain)
------------	----------------

Transparent cover or door	yes
---------------------------	-----

Cover type	Door
------------	------

Door locking	without
--------------	---------

Type of door closing	Latch
----------------------	-------

Door leave	single
------------	--------

Door quantity	1
---------------	---

Identification od protection index	65
------------------------------------	----

Interlockable	no
---------------	----

Materials

RAL colour	RAL 7035 - Light grey
------------	-----------------------

Colour	light grey
--------	------------

Colour	light grey
--------	------------

Material	plastic
----------	---------

Type of surface treatment	untreated
---------------------------	-----------

Dimensions

Depth of installed product	151 mm
----------------------------	--------

Internal depth	151 mm
----------------	--------

Height of installed product	677 mm
-----------------------------	--------

Width of installed product	310 mm
----------------------------	--------

Width in division units	48
-------------------------	----

Technical Properties

Thickness of sidewall material	2,5 mm
--------------------------------	--------

Installation, mounting

Suitable for outdoor use	yes
--------------------------	-----

Connection

Number of conduit inlets	12
--------------------------	----

Accessories included

Mounting plate included	no
With lock	no

Equipment

Number of openings for flange plates	46
Number of rows	4
Quantity of section in width	1
Can be accessorized	yes
Quantity of rails	4

Standards

European directive WEEE	concerned
-------------------------	-----------

Safety

Protection class	isol.class II
Protection index IP	IP65
IK protection code against mechanical impacts	IK08
Halogen free	yes
Ultraviolet resistant	yes

Use conditions

Operating temperature	-25 40 °C
-----------------------	-----------