



Sm.distr, golf, flush, 72M, trans. door DZA

VF418TT

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

With a pipe-in lead	yes
---------------------	-----

Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

Main electrical features

Nominal voltage	400 V
-----------------	-------

Cover, door

Cover type	Closed (plain)
------------	----------------

Transparent cover or door	yes
---------------------------	-----

Cover type	Door
------------	------

Door locking	without
--------------	---------

Type of door closing	Latch
----------------------	-------

Door leave	single
------------	--------

Door quantity	1
---------------	---

Identification od protection index	40
------------------------------------	----

Interlockable	no
---------------	----

Materials

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Colour	white
--------	-------

Colour	pure white
--------	------------

Material	plastic
----------	---------

Type of surface treatment	untreated
---------------------------	-----------

Dimensions

Insertion depth	72 mm
-----------------	-------

Depth of installed product	97,5 mm
----------------------------	---------

Internal depth	97,5 mm
----------------	---------

Height of installed product	688 mm
-----------------------------	--------

Built-in height	652 mm
-----------------	--------

Built-in width	426 mm
----------------	--------

Technical Properties

Width of installed product	460 mm
Width in division units	18

Installation, mounting

Suitable for outdoor use	no
--------------------------	----

Accessories included

Mounting plate included	no
With lock	no

Equipment

Number of rows	4
Quantity of section in width	1
Can be accessorized	yes
Quantity of rails	4

Safety

Protection class	isol.class II
Protection index IP	IP40
Halogen free	yes
Ultraviolet resistant	no

Use conditions

Operating temperature	-25 40 °C
-----------------------	-----------