



# DULAR

## Residential Downlights

  
**TRITONE**  
Colour  
Changeable

  
**DIM**  
Phase Cut  
Dimming

  
**UGR<19**  
Beam  
Angle

  
**35,000hr**  
Expected  
Lifetime

  
**5yr**  
Warranty

**For comfortable, low glare environments.**

DULAR offers an all-in-one solution. Complete with built-in dimmable driver, DULAR also has a recessed design which offers low glare output that enhances visual comfort.

### Features

- Fixed and adjustable versions
- Low glare, recessed design
- Tritone selectable
- Built-in dimmable driver
- IP44 from below

### Benefits

- Increased application flexibility
- Enhanced visual comfort
- Reduced SKUs and inventory levels
- Energy saving and comfort
- Perfect for wet areas

## Product Overview

| POWER | LUMENS | EFFICACY | CCT   | CUTOUT | WEIGHT | FASCIA         | SAP CODE | PRODUCT CODE                                 |
|-------|--------|----------|-------|--------|--------|----------------|----------|--|
| 8W    | 820 lm | 102 lm/W | 3000K | Ø90mm  | 0.25kg | White<br>Black | 2001850  | <b>DULAR-FIX-TRI</b><br><b>DULAR-FIX-BLK</b> |
|       | 930 lm | 116 lm/W | 4000K |        |        |                | 2001892  |  |
|       | 880 lm | 110 lm/W | 5700K |        |        |                | 2001893  |  |
| 8W    | 820 lm | 102 lm/W | 3000K | Ø90mm  | 0.25kg | White<br>Black | 2001856  | <b>DULAR-ADJ-TRI</b><br><b>DULAR-ADJ-BLK</b> |
|       | 930 lm | 116 lm/W | 4000K |        |        |                | 2001893  |  |
|       | 880 lm | 110 lm/W | 5700K |        |        |                | 2001893  |  |

**FIX** = Fixed    **ADJ** = Adjustable    **TRI** = Tritone    **BLK** = Black

### SPECIFICATIONS

|                                |                                    |                                       |  |
|--------------------------------|------------------------------------|---------------------------------------|--|
| <b>Body Material:</b>          | Aluminium and Polycarbonate        | <b>Driver:</b>                        | Integral                                   |
| <b>Diffuser Material:</b>      | Polycarbonate (Multifaceted)       | <b>Power Lead:</b>                    | 1m Flex & Plug                             |
| <b>Fascia colour:</b>          | White: RAL 9003<br>Black: RAL 9011 | <b>Input:</b>                         | 220-240V, 50/60Hz                          |
| <b>IP Rating (Fixed):</b>      | Front: IP44<br>Body: IP20          | <b>Electrical Classification:</b>     | Class 2                                    |
| <b>IP Rating (Adjustable):</b> | Front: IP20<br>Body: IP20          | <b>Power Factor:</b>                  | >0.9                                       |
| <b>IC Rating</b>               | IC-4 (Fixed only)                  | <b>Protection:</b>                    | Overload / Short Circuit                   |
| <b>Beam Angle:</b>             | 45°                                | <b>Lifespan:</b>                      | >35,000hrs @Ta25°C (L70)                   |
| <b>Gimbal:</b>                 | 0-30° (Adjustable only)            | <b>Operating Ambient Temperature:</b> | -20 to 45°C                                |
| <b>CRI:</b>                    | >80 (>90 option)                   | <b>Smart:</b>                         | KASTA Compatible                           |
| <b>UGR:</b>                    | <19 (Fixed only)                   | <b>Dimming:</b>                       | Phase-Cut Dimmable (Trailing Edge, 1-100%) |
| <b>SDCM:</b>                   | <5 (<3 option)                     |                                       |  |

### APPLICATIONS

Residential  
Retail  
Showrooms

### ACCESSORIES

**Surface Mount Kit:**  
**SM-ENC-DL**  
(SAP 2001870)  
(DULAR-ADJ-TRI only)



**Suspension Kit:**  
**SM-ENC-SUSKIT**  
(SAP 2001871)  
(DULAR-ADJ-TRI only)



DULAR-FIX-TRI



DULAR-FIX-BLK





DULAR-ADJ-TRI





DULAR-ADJ-BLK

### DIMENSIONS



DULAR-FIX-TRI



DULAR-ADJ-TRI

FIND OUT MORE:

