




# SKYLUX

SKYLUX-150W  
SAP CODE: 2001897



150W, 0-10V Dimming,  
Wide voltage range,  
110° Beam angle LED  
Highbay


A versatile, cost effective LED  
Highbay for lighting large  
industrial spaces

### Accessories

BRACKET; MICROWAVE SENSOR;  
REMOTE



Photometric  
Diagram



Unit: cd  
- C0/180 114.1deg  
- C90/270 115.7deg

## KEY INFORMATION

Lumen Output	24140lm
Input Power	150W
Dimming Options	0-10V Dimming
Trim Colour	BLACK
Warranty	5yr
IP Rating	IP65
IK Rating	IK08
Rebate Scheme Approvals	VEET; REES; IPART

## PHOTOMETRIC

Efficacy	161lm/W
LED	SMD
CCT	5000K
CRI	>70
Beam Angle	110°

## ELECTRICAL

Driver	Integral
Supply Input	100-277V, 50/60Hz
Driver Output Voltage	120VDC
Power Factor	>0.9
LED Input Current (nominal)	1300mA
Useful life @Ta25° (L70)	50,000hr

## CONSTRUCTION

Housing	Aluminium ADC12
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	1.5m Flex & Plug
Total Weight	4kg
Dimensions	Ø360 x 185mm
Operating Ambient Temp.	-35 to 50°C
Electrical Classification	Class 1