


Data Sheet

Fanlight


CAT NO. **R620, STANDARD VERSION**
R620LED, LED VERSION



Cat No	R620 Fanlight	R620LED LED Fanlight
Colour	White	
Supply voltage	230-240V a.c.	
Fan Power Consumption	38W	
Maximum Rated Power	113W	49W
Fan Airflow	300m ³ /h	
Light	75W max	600lm (equivalent to 50W GLS)
Lamp	BC Lampholder (lamp not included)	LED panel
Protrusion from ceiling	90mm	
Projection into ceiling	130mm	
Ceiling Cutout Size	300mm diameter	
Impeller diameter	200mm	
Weight	3kg	

Fanlight

CAT NO. **R620, STANDARD VERSION**
R620LED, LED VERSION



Single product (QTY 1)			
Cat No	Weight	Dimensions	Barcode
R620	2.91kg	380mm x 380mm x 285mm	9310539617206
R620LED	2.62kg	380mm x 380mm x 225mm	9321001433989

Outer box (QTY 2)			
Cat No	Weight	Dimensions	Barcode
R620	5.82kg	380mm x 380mm x 450mm	9321001168201
R620LED	5.24kg	380mm x 380mm x 450mm	9321001433996

- R620LED Fanlight includes an integrated LED light panel
- R620 Fanlight includes a BC lampholder
- Powerful 38W fan with 300m³/h airflow
- Wide air vents for effective vapour, fumes and odour extraction
- The light or exhaust fan can be used separately or together
- Quick and quiet - expels steam and room odours
- The LED Fanlight has excellent light distribution due to a full width diffuser and an integrated 11W LED panel light
- Easy to install and remove diffuser for cleaning
- 300mm diameter round cut out for easy installation
- Ceiling mounted
- Comfortable bright light for general illumination
- Ideal for bathrooms, laundries and kitchens

HPM Legrand - AUS
1300 369 777
www.hpm.com.au
ABN 31 000 102 661

HPM Legrand - NZ
0800 476 009
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.