# CONCEPT LED CEILING FAN



Matt White with White Blades

#### Installation Locations:

Coastal, indoor and outdoor undercover (provided the fan is fully undercover). Also suitable for installation in a pergola or outside in a sheltered area, protected from wind and rain.

#### **Recommended Height:**

There should be at least 2.1m between the lowest point of the fan blades and the floor.

#### Motor:

153mm x 15mm 16 Poles AC motor Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life

## Top Canopy & Downrod:

Materials: Die-Cast Aluminium

#### **Product Range:**

CL506 White w White Blades CL507 Matt Black w Matt Black Blades CL508 Brushed Aluminium w Silver Blades

#### Blades:

Sizes: 1320mm (52") Materials: Polymer Blades Blade Pitch: 11°

#### Extra Information:

Introduced into the HPI range in 2022 Reversible

#### Warranty:

3 years standard "In-Home" warranty 3 years "Parts Only" warranty on motor (excluding labour)

1 year warranty applies when the fan or relevant part is used in any non-domestic applications. Integrated light kits on AC ceiling fans are covered by 2 years

warranty.

#### Airflow CMH:

14.096 on High Speed (Speed 3)

14,090 011 fight Speed (Speed S)				5 LOGIC (4 Speed -
Lo	ow Medi	um High		veger Tone Filter U
RPMS 84	121	192		ZF-1050 Notch Filte ZF-750 Notch Filter
WATTS 12	.5 26	62		
Dimensions			C.	
A	В	С	D	E
1320mm	365mm	n 270mr	n 173mm	56mm

## Standard Canopy Cover:

Suitable for flat ceiling and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values: 3.5µF & 2µF

Weight Including Packaging: Complete fan: 8.5 kg

Packaging Dimensions (mm): Complete Fan: 617L x 282W x 315H

Light Fitting: 18W CCT LED light (dimmable)

**Colour Temperatures:** 3000K, 4000K & 6000K

### Accessories (Supplied separately):

Down Rod 26mm diameter (includes wire harness) 010 91cm White Downrod 013 91cm Black Downrod 018 91cm B/Alum Downrod 020 180cm White Dowrod 023 180cm Black Dowrod 028 180cm B/Alum Dowrod

38° Ceiling Kit (for pitched ceilings) 080 Ceiling Kit White 38 082 Ceiling Kit Painted Silver 38° 083 Ceiling Kit Black 38

009 T-Hook for ceiling roses

AC Remote Control Units A2002 Konetik (3 speed - non dimming remote) A2003 Logic (4 speed - dimming remote)

Init ter Noise Suppressor er Noise Suppressor