

Xtreme **Lx II**

QUICK FIT BRACKET!

iQL



FLOOD LIGHT SERIES



TECHNICAL

Light Source	Lumileds
Body	Die Cast Aluminium Alloy
Body Colour	RAL9004 Black
Fasteners	Stainless Steel
Colour Temperature	3000K, 5700K
Average LED & Control Gear Life	L 70 > 50,000hrs Ta 25 (degree C)
Beam Angle	Asymmetrical
Efficacy	Up to 150 Lm/w
CRI	> 80

ELECTRICAL

Power Supply Constant Current	100-277Vac
Power Factor	> 0.9
Connection Lead	3m Rubber Flex & Plug (10, 20, 30 50w only)
Ingress Protection Rating	IP65
Impact Rating	IK08
Certification	RCM
Warranty	3 Years



CONSTRUCTION FEATURES

- IK08 tempered glass over PC Lens for superior light output and protection
- Angle bracket for ease of installation
- UV stabilised powder coating

ORDER CODES

Model	Wattage	Light Colour*	Lumens	Weight	Size (in mm)		
					A	B	C
XLX10WW	10 watts	3000K	1,300Lm	0.68kgs	167	106	41
XLX10CW	10 watts	5700K	1,300Lm	0.68kgs	167	106	41
XLX20WW	20 watts	3000K	2,600Lm	0.68kgs	167	106	41
XLX20CW	20 watts	5700K	2,600Lm	0.68kgs	167	106	41
XLX30WW	30 watts	3000K	3,900Lm	1.67kgs	280	193	44
XLX30CW	30 watts	5700K	3,900Lm	1.67kgs	280	193	44
XLX50WW	50 watts	3000K	6,500Lm	1.67kgs	280	193	44
XLX50CW	50 watts	5700K	6,500Lm	1.67kgs	280	193	44
XLX80CW	80 watts	5700K	10,400Lm	3.85kgs	297	195	53
XLX100CW	100 watts	5700K	13,000Lm	3.85kgs	297	195	53
XLX150CW	150 watts	5700K	19,500Lm	6.12kgs	354	262	53
XLX200CW	200 watts	5700K	26,000Lm	6.12kgs	354	262	53
XLX240CW	240 watts	5700K	36,000Lm	9.95kgs	277	160	409
XLX360CW	360 watts	5700K	54,000Lm	17.05kgs	406	427	424



SMARTER LIGHTING SOLUTIONS

IQL Australia
 6/24 Yalgar Rd, Kirrawee NSW 2232
www.iqlighting.com.au
 1300 475 444

Technical Data sheets available on request. Model appearance may vary.
 July 2020 specifications are subject to change without prior notice.