760237046 | CPP-SDDM-SL-1U-24

Discrete Distribution Module Panel, SL, STP, 1U, 24 port



Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio CommScope®

Product Type RJ45 patch panel

General Specifications

ANSI/TIA Category 6 | 6A

Cable Type Shielded

Color Black

Modules, quantity 0

Panel StyleStraightRack TypeEIA 19 in

Rack Units 1

Total Ports, quantity 24

Dimensions

 Height
 44.45 mm | 1.75 in

 Width
 482.6 mm | 19 in

 Depth, with cable management
 119.38 mm | 4.7 in

Material Specifications

Material Type High-impact, flame retardant, thermoplastic | Powder-coated steel

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \text{ (+14 }^{\circ}\text{F to } +140 \,^{\circ}\text{F)}$

COMMSC PE°

760237046 | CPP-SDDM-SL-1U-24

Storage Temperature $-40 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to $+158 \,^{\circ}\text{F}$)

Flammability Rating UL 94 V-0

Safety Standard RCM | UL | cUL

Packaging and Weights

Packaging Material Eco-friendly, Single-use Plastics-free

Packaging quantity 1

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



