

Product data sheet

Characteristics

MX9E2215S

Switchboard enclosure, MAX9, type 2, 2 row,
30 ways, surface mount



Main

| | |
|---------------------------------|---|
| Range | MAX9 |
| Product brand | Clipsal |
| Product or component type | Enclosure |
| Device application | Distribution |
| Number of 18 mm modules per row | 15 |
| Provided equipment | Earthing bar Neutral bar Circuit identification label Blanking plate |
| Colour | White electric (RAL 9003) |
| Door type | Plain door - right and left |

Complementary

| | |
|--------------------------------|-------------------------|
| Enclosure mounting | Surface |
| Number of horizontal rows | 2 |
| [Ue] rated operational voltage | 240/415 V AC |
| [In] rated current | 100 A |
| [Ui] rated insulation voltage | 500 V |
| Number of ways | 30 ways |
| Cable entry | Knock-out cable entries |
| Type of rail | DIN |
| Enclosure material | Housing: plastic |
| Width | 376 mm |
| Height | 392 mm |
| Depth | 120 mm |

Environment

| | |
|-------------------------|-------------------------------|
| Standards | AS/NZS 61439-3 AS/NZS 3000 |
| Fire resistance | 650 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK05 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 4.02 kg |
| Package 1 Height | 12.5 cm |
| Package 1 width | 39.5 cm |
| Package 1 Length | 41 cm |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 72 |
| Package 2 Weight | 305 kg |
| Package 2 Height | 165 cm |

| | |
|------------------|--------|
| Package 2 width | 80 cm |
| Package 2 Length | 120 cm |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |