

Catalogue No: **D7M-F4**

PUSHBUTTON 22.5mm METAL FLUSH RED

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Sprecher + Schuh D7 Pushbuttons and Pilot Lights > D7 Momentary Pushbuttons > D7 Flush Momentary Pushbuttons



Button metal flush Red



Representative Photo Only
(actual product may vary based on configuration selections)

- D7 pilot devices offer maximum flexibility and a wide choice for all 22.5mm operator applications with all type (e-stops, selector switches, pushbuttons, pilot lights and more), colour and contact configurations.
- Aesthetically appealing and modularly designed to make assembly and interchangeability easy.
- Operators exhibit low profile and stylish appearance while maintaining the rugged performance necessary for demanding environments
- D7P is a plastic operator with a captive black plastic front bezel. Constructed of high grade thermoplastics, the D7P operators provide strong chemical resistance making them suitable for use in different environments
- D7M has a die-cast zinc housing and mounting ring for rugged durability. Finished with corrosion resistant chrome plating, the D7M also features a captive shiny metal bezel for a polished appearance.

SPECIFICATIONS

| | |
|--|------------------------|
| Component Type Pushbutton and Pilot Lights | Pushbutton |
| Operator Type | Pushbutton, Flush type |
| Operator Action | Momentary action |
| Diameter, Operator | 29.6 mm |
| Colour, Operator | Red colour |
| Operator Insert Type | Red insert |
| Material, Bezel | Zinc |
| Coupling Plate Included | No Y / N |
| Diameter, Mounting Hole(s) | 22.5 mm |
| Contact Block Included | No |
| Illuminated | No Y / N |
| Tightening Torque, Nominal | 4.4 Nm |
| Electrical Service Life at Un, In | 500000 cycles |
| Mechanical Service Life | 10000000 cycles |
| RoHS Approved | Yes |
| CE Marked | Yes |
| Operating Temperature, Max | 70 °C max |
| Operating Temperature, Min | -25 °C min |
| Storage Temperature, Max | 85 °C max |
| Storage Temperature, Min | -25 °C min |
| Relative Humidity, Min | 50 %RH |
| Relative Humidity, Max | 95 %RH |
| Shock Acceleration (Max.) | 100 g |
| Shock Duration (Max.) | 11 ms |
| Vibration Acceleration (Max.) | 10 m/s ² |
| Vibration Displacement (Peak to Peak Max.) | 1.52 mm |
| Vibration Frequency, Operational (Max.) | 2000 Hz |
| Vibration Duration (Max.) | 180 min |

Catalogue No: **D7M-F4**

PUSHBUTTON 22.5mm METAL FLUSH RED

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Sprecher + Schuh D7 Pushbuttons and Pilot Lights > D7 Momentary Pushbuttons > D7 Flush Momentary Pushbuttons



| | |
|----------------------|--|
| Standards Compliance | NEMA ICS-5 UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 EN 418 |
|----------------------|--|

| | |
|----------------|------------------------------|
| Certifications | UL UR CSA CCC CE |
|----------------|------------------------------|

| | |
|--------------------|--|
| Shipping Approvals | RINA (Registro Italiano Navale) ABS (American Bureau of Shipping) Lloyd's Register of Shipping |
|--------------------|--|

REFERENCES

| | |
|-------------------|---|
| IECEX Certificate | - |
|-------------------|---|

| | |
|-------------------------------------|---|
| Supplier Declaration of Conformity: | - |
|-------------------------------------|---|

| | |
|---------------------|---|
| Installation Guide: | - |
|---------------------|---|

| | |
|--------------|---|
| User Manual: | - |
|--------------|---|

| | |
|-------------------------|--|
| Manufacturer Datasheet: | Series D7_Manufacturer Datasheet |
|-------------------------|--|

| | |
|---|---|
| Manufacturer Catalogue & Product Selection: | - |
|---|---|