

Figure 8

SPK-TRP 2X 2.6 CL 1HM

Contact
Sales
Phone: 1300 CABLES
olexcustomerservice@nexans.com

Nexans Ref.: JSF2.6CL1


EAN 13: 9322576293886

Two stranded bare copper conductors, PVC insulated (parallel webbed)

DESCRIPTION

Applications Suitable for use in audio systems for low and high power speaker connections, security applications.

Construction Two stranded bare copper conductors, PVC insulated (parallel webbed) available with standard or oxygen free copper.



Conductor flexibility
Flexible

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 2/12/21 www.olex.com.au Page 1 / 2

Figure 8

SPK-TRP 2X 2.6 CL 1HM

Contact
Sales
Phone: 1300 CABLES
olexcustomerservice@nexans.com

CHARACTERISTICS

Construction characteristics

Conductor flexibility	Flexible
Conductor material	Oxygen-free copper
Conductor shape	Circular

Dimensional characteristics

Approximate weight	8.1 kg/100m
Conductor cross-section	2.6 mm ²
Nominal Overall Size (mm)	9.0 x 4.5
Nominal insulation thickness	1.0 mm
Stranding (No./mm)	84/0.20

Electrical characteristics

Max. DC resistance of the conductor at 20°C	7.4 Ohm/km
Rated Voltage U ₀ /U	-
Voltage drop single phase at 45°C	16.3 mV/A.m