



VANDAL RESISTANT

RHINO 66

SERIES

IQL



LINKABLE
NON-FLICKER

VANDAL & IMPACT RESISTANT LED BATTEN



TECHNICAL

Body	Aluminium, Polycarbonate diffuser
Colour Temperature	5000K (also available in NSP Amber* options)
Average LED and Control Gear Life	>78,000 hrs (L70/Ta25c)
Beam Angle	120° degrees
Efficacy	130Lm/W
CRI	> 80
Max Junction Temperature	150C
Cooling	Conduction, Convection
Operating Range Tc	-35°C – 50°C
Thermal Management	Aluminium Heatsink



ELECTRICAL

Power Supply	Non-Flicker LED Driver
Protection	Over Voltage, Short Circuit and Over Temperature
Power Factor:	> 0.96
Total Harmonic Distortion (THD)	<15%
Ingress Protection Rating:	IP66
Impact Rating	IK10
Certification	RCM, EMC, CE,
Warranty	3 Years



ORDER CODES

Model	Wattage	Light Colour	Lumens	Weight	Size (in mm)		
					A	B	C
RWP66-600	20 watts	5000K	2,600Lm	1.9kg	600	83	63
RWP66-600-MS	20 watts	5000K	2,600Lm	1.9kg	600	83	63
RWP66-1200	40 watts	5000K	5,200Lm	3.3kg	1200	83	63
RWP66-1200-MS	40 watts	5000K	5,200Lm	3.3kg	1200	83	63

ACCESSORIES

RWP66-ANGCLIP	Adjustable Angle Change Clip
RWP66-BR	45 Degree Metal Bracket
RWP66-SUSCAB	Suspending Steel Cable 1m Length

Technical Data sheets available on request. Model appearance may vary.
July 2020 specifications are subject to change without prior notice.



SMARTER LIGHTING SOLUTIONS
IQ Lighting Australia
 6/24 Yalgar Rd, Kirrawee NSW 2232
 www.iqlighting.com.au
 1300 475 444



*NatureSpec wildlife safe amber light available on request