

# Product datasheet

Specifications



Acti9, MSC Chassis 3PH, 250A,  
18mm for iC60 MCB & RCBO, 60  
poles, Dual Feed

C325603

## Main

Range	Acti9
Device Short Name	MSC 18
Product Or Component Type	Chassis
Device Application	Distribution

## Complementary

Range Compatibility	Acti9 Acti9 Isobar B distribution board
[In] Rated Current	250 A
Rated Voltage	415 V AC 50 Hz
Short-Circuit Withstand	25 kA 0.1 s
[Icw] Rated Short-Time Withstand Current	25 kA
[Ui] Rated Insulation Voltage	500 V
[Uimp] Rated Impulse Withstand Voltage	6 kV
Number Of Ways	1 way (incomer) - 3P 60 ways (outgoer)
Outgoer Pole Capacity	60 x 18 mm
Length	542 mm
Width	215 mm

## Environment

Standards	AS/NZS 61439
-----------	--------------

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations