Product data sheet Characteristics

EY56C310LE

Easy56, Switched Socket, 3 Pin, 10A, 250V, Less Enclosure



Main Product name Easy56 Product or component Switch and socket-outlet type Device short name EY56C310LE Plug, socket category Low voltage Poles description 1P + N + E Control type Rotary knob Rotary handle 2 padlocks 8 mm padlocking Network type AC Outlet standard Australian/New Zealand

Complementary

Mounting mode	Surface mounted
Plug, socket, control station shape	Straight
[In] rated current	10 A
Pin number	3 pins
Shape of pin	Flat
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Protection type	Without protection
Material	Polycarbonate
Contacts material	Pins: phosphor bronze
Connections - terminals	Screw terminals
Cable cross section	1.56 mm²
Net weight	0.68 kg
Height	203 mm
Width	101 mm
Depth	65 mm
Colour	Body: grey (RAL 7035) Rotary handle: dark grey

Environment

Standards	AS/NZS 3133
	AS/NZS 3112
Quality labels	RCM
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C
Ambient air temperature for storage	-2575 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	19.0 cm	
Package 1 Width	10.5 cm	
Package 1 Length	20.5 cm	
Package 1 Weight	399.0 g	

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	

Life Is On