

Product data sheet Characteristics

EY56C520

Easy56, Switched Socket, 5 Pin, 20A, 500V



Main Product name Easy56 Product or component Switch and socket-outlet type Device short name EY56C520 Low voltage Plug, socket category Poles description 3P + N + E Control type Rotary knob Rotary handle 2 padlocks 8 mm padlocking AC Network type Outlet standard Australian/New Zealand

Complementary

Mounting mode	Surface mounted
Plug, socket, control station shape	Straight
[In] rated current	20 A
Pin number	5 pins
Shape of pin	Tubular
[Ue] rated operational voltage	500 V
Network frequency	50 Hz
Protection type	Without protection
Material	Polycarbonate
Contacts material	Pins: brass
Connections - terminals	Screw terminals
Cable cross section	116 mm²
Cable entry number	2 x M25
	1 x M32
Net weight	0.82 kg
Height	203 mm
Width	101 mm
Depth	101 mm
Colour	Body: grey (RAL 7035) Rotary handle: dark grey

Environment

Standards	AS/NZS 3123 AS/NZS 3133
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C
Ambient air temperature for storage	-2575 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	11.2 cm	
Package 1 Width	10.8 cm	
Package 1 Length	21.2 cm	
Package 1 Weight	928.0 g	

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	

Life Is On