

Product data sheet Characteristics

EY56SO310LE

Easy56, Socket, 3 Pin, 10A, 250V, Less **Enclosure**

AC



Main Product name Easy56 Product or component Socket-outlet type Device short name EY56SO310LE Plug, socket category Low voltage Poles description 1P + N + E

Australian/New Zealand

Complementary

Complementary		
Mounting mode	Surface mounted	
Plug, socket, control station shape	Straight	
[In] rated current	10 A	
Pin number	3 pins	
Shape of pin	Flat	
[Ue] rated operational voltage	250 V	
Network frequency	50 Hz	
Material	Polycarbonate: cover	
Contacts material	Pins: phosphor bronze	
Connections - terminals	Screw terminals 1.56 mm² rigid or stranded cable	
Wire stripping length	10 mm	
Net weight	0.216 kg	
Height	101 mm	
Width	101 mm	
Depth	65 mm	
Colour	Grey (RAL 7035)	

Network type

Outlet standard

Environment

Standards	AS/NZS 3112	
Quality labels	RCM	
IP degree of protection	IP66 conforming to AS 60529	
Ambient air temperature for operation	-2575 °C	
Ambient air temperature for storage	-2575 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.8 cm	
Package 1 Width	10.0 cm	
Package 1 Length	10.0 cm	
Package 1 Weight	217.0 g	

EU RoHS Directive

Under investigation